



Pollux Series

GL-Panel Light 595 x 595

● Features




- Elegant structure, designed to dissipate heat
- Slim and low profile design
- No Mercury, No UV and No IR light radiation
- RoHS compliance
- Ideal replacement for tube lights or grid lights
- Power Consumption: 50W
- Up to 45% less power consumption vs. Fluorescent Lamps
- 30,000hrs Lifespan (6 x longer than Fluorescent Lamps)
- Low heat output
- 2 Years Warranty

● Specifications

Model	GL-PL0606A-WW	GL-PL0606A-NW	GL-PL0606A-CW
Energy Used	50W	50W	50W
Rated Life	30,000 Hours	30,000 Hours	30,000 Hours
CCT	3,000K	4,000K	6,000K
Input Voltage	100 - 240V AC	100 - 240V AC	100 - 240V AC
Luminous Flux (lm)	2400lm (Typ.)	2400lm (Typ.)	3400lm (Typ.)
CRI	>75	>75	>70
Dimension	595 x 595 x 13mm	595 x 595 x 13mm	595 x 595 x 13mm
Beam Angle	120°	120°	120°

Remark : 600 X 600mm Panel Light is available upon request.

● LED Driver Suggestions : LCB221-50



FCC Certificate

- 300 x 300mm
 - 300 x 600mm
 - 600 x 1200mm
- coming soon

